



**Specifications Noxion LED Downlight Slim V2.0 20W 2000lm 120D - 830 Warm White | 225mm - Cutout 200mm - IP44**

[View Product](#)

## General Information

|                          |                                                                          |
|--------------------------|--------------------------------------------------------------------------|
| SKU                      | 238900                                                                   |
| EAN                      | 8719157014892                                                            |
| Brand                    | Noxion                                                                   |
| Manufacturer Name        | Noxion LED Downlight Slim V2.0 IP44 20W 3000K Cutout Ø200mm Frame Ø225mm |
| Any Lamp all-in warranty | 6 Years                                                                  |
| Average Lifetime (h)     | 50000                                                                    |

## Technical Information

|                             |                   |
|-----------------------------|-------------------|
| Emergency Lighting          | No Emergency Unit |
| Tiltable                    | No                |
| Technology                  | LED Integrated    |
| Wattage                     | 20                |
| Voltage (V)                 | 220-240           |
| Dimmable                    | Not Dimmable      |
| Colour Code                 | 830 Warm White    |
| Colour temperature (Kelvin) | 3000 Warm White   |
| Colour Rendering (Ra)       | 80-89             |
| Colour of Light             | White             |
| Light colour options        | Single Color      |
| Driver Included             | Yes               |

|                          |                                       |
|--------------------------|---------------------------------------|
| Beam Angle (degree)      | 120                                   |
| Luminous Flux (Lumen)    | 2000                                  |
| Luminous Efficacy (lm/W) | 100                                   |
| Power factor             | >0.90                                 |
| Installation Depth (mm)  | 19                                    |
| Unified Glare Rating     | < 28 - for hallways and storage rooms |
| Optical Cover            | PC (Polycarbonate)                    |
| Product Type Category    | LED Downlight                         |

## Fixture Information

|                        |                   |
|------------------------|-------------------|
| Mounting Method        | Recessed          |
| Cut out (mm)           | 200               |
| IP-rating              | IP44              |
| Impact Protection (IK) | IK02 - 0.20 joule |
| Operating Temperature  | -20 to +40        |
| Housing                | Aluminium         |
| Colour of the Fixture  | White             |
| Colour of material     | White             |
| Series                 | Slim              |

## Dimensions

|               |     |
|---------------|-----|
| Height (mm)   | 26  |
| Diameter (mm) | 225 |

 **Sensor Information**  **Customised quotation**

Type of sensor



Up to **7 years warranty**

No Sensor



**Easy return process**